

Dual 10.4" Multi Display

Broadcast Monitor



A high-definition 2-way multi-display with audio-presence meters, UMD and Tally display, adjustment of individual display characteristics and signal loop-out.

Ideal for 19" rack mounting in high quality broadcast installations.

Features

- » Dual 10.4" independent displays
- » Colorimetry set to broadcast standard
- » Input options: SDI, HDSDI
- » Extensive image controls
- » Adjustable reverse gamma
- » Adjustable aspect ratio
- » Adjustable colour temperature
- » Internal test screen generator
- » 19" Rack mount kit
- » Selectable source sync
- » Colour channel monitoring
- » Overscan control
- » On-screen audio presence meters
- » UMD and Tally information
- » Black stretch
- » RGB channel separation
- » Graphic mode
- » Safe area cages
- » Individual RGB gain
- » Reveal blanking



SPECIFICATIONS

Feature	
Input formats	Auto Detect - Single Link SDI/HDSDI: SMPTE 259M, 292M
Viewable area	210 x 158 mm
Resolution	1024 x 768
Pixel pitch	0.21 x 0.21 mm
Brightness	400 Cd/m ² without filter glass
Contrast ratio	1200:1
Viewing angle	176°/176° Horizontal/Vertical
Response time	10ms (Grey to Grey)
Display Aspect Ratio	4:3
Displayable aspect ratio	4:3, 14:9, 15:9, 16:9, 16:10
Filter glass	Anti glare
Picture locking	Received signal, free run
Control and setup	Handheld IR remote & button switches on front panel
Picture controls	Brightness, Contrast, Sharpness, Hue, Saturation
Colour temperature	5400, 6500, 7200, 8200, 9200
Overscan	Adjustable
Audio presence meters	Any four of up to 16 embedded audio channels
UMD	Colour, 16, 24, dynamic width, variable position, picture blank area, colours, RS422: TSL, Grass Valley protocols. IP controllable.
Tally	Red, green blocks. Contact closure on RS422 9-way Din or GPI RJ45.
Gamma	1, 2, 2.22, 2.35, 2.5
Backlight	Adjustable
Black stretch	Adjustable
Display mode	Yes (Red All, Green All, Blue All, Red Only, Green Only, Blue Only, Invert)
Safe area cages	Yes
RGB gain	Yes
Reveal blanking	Yes
Dimensions	460 (w) x 250 (H) x 88 (D) mm
Weight	3Kg
Power consumption	50W
Tilt	10° Down and 5° Up from Vertical
Mounting	4 x M4 fixings on each side & rack mount kit
Part number	VUT10X2VX323F

Vutrix, Vutrix House, Unit 1 & 2, Red Lodge Business Park,
Weston-super-mare, Somerset, BS24 7TN, England

Tel: +44 (0) 1934 529932
sales@vutrix.com

www.vutrix.com